

COMTELCO

Technical Specification

BSM800UWB

806-960 MHz Unity Gain

BASE STATION ANTENNA

Reliable Performance: Rated at 250 watts and unity gain across the 806-960MHz band, this antenna will provide years of continuous service.

Rugged Construction: The radiating elements are supported internally and constructed of copper alloy. They are then encased in a fiberglass radome for total environmental protection.

Weatherproof: The fiberglass radome is ultraviolet inhibited. The brass mounting sleeve is triple plated chrome for unsurpassed weather protection.

Lightweight: These antennas are lightweight at less than 4 lbs. but are designed to withstand winds in excess of 125 MPH.

Simple Installation: Using the optional 1" 14THD mounting nut, this antenna can be installed quickly on an available L bracket.



ELECTRICAL SPECIFICATIONS:

FREQUENCY:	806-960MHz
GAIN:	Unity
VERTICAL BEAMWIDTH:	70°
BANDWIDTH:	154MHz @ <2.0:1
POWER RATING:	250 watts
IMPEDANCE:	50 ohms

MECHANICAL SPECIFICATIONS:

ANTENNA LENGTH:	20"
RADIATOR:	Internal copper alloy elements
RADOME:	White UV inhibited fiberglass
MOUNT:	1" 14THD marine type
MOUNTING SLEEVE:	Chrome plated brass, female
WEIGHT:	3 lbs.
FLAT PLATE AREA:	.083 ft ²
WIND RATING:	125 MPH
LATERAL THRUST:	5.6 lbs.

Vertical Pattern

