SPECIALTY MOUNTS

TMBM, TMBC Trunk Mounting Bracket: Stainless steel bracket with stainless screws. 3/4" or 3/8" hole and black or brite finish available. 3/8" version accepts C mount. Designed for permanent installation on trunk lid.

MMM Commercial Mirror Bracket: Mirror bracket with 3/8" hole to accept C mount. Black powder coat finish.

MMNMO Complete Mirror Mount: Mirror bracket with NMO mount and 17 feet of RG58 coax. Black powder coat finish.

BSMN Mirror Mount NMO: Mirror bracket with NMO mount terminated with an “N” type connector. Black powder coat finish.



UNIBKT: Universal mounting bracket with .625” dia. hole. (accepts “N” type connector) Black powder coat finish.

UTBM Universal Thick Body Mount: This mount allows for installation through body surfaces up to 5/8" thick such as fiberglass. The UTBM mount terminates as a MINI-UHF female connector. Optional cable assemblies are available to fit most applications.

UTCM Universal Ceiling Mount: Allows for easy installation of NMO based products through standard ceiling tile. Comes complete with white ground plane plate for UHF, 800MHz, 1.8GHz, 2.4GHz and 5GHz ceiling mounted products.



TAUHF, TAN: Thick body NMO mount adapters. TAUHF terminates in a SO239 type connector and mates with a PL259 type male. TAN terminates as an “N” connector.